



I N P H Y S I C S W E T R U S T

## 4activeEQ-AVAD 3

### Detector for audio/visual signals from the vehicle

- ✓ detects acoustic and optical warnings and messages from inside the vehicle
- ✓ using high-performance camera and microphone
- ✓ ideally suited for AEB, FCW, SAS, LSS in compliance with EuroNCAP

### Successfully used by most manufacturers, OEMs and test laboratories

- ✓ very fast, top-quality processor for sound and image processing
- ✓ up to 8 patterns, colours and colour search areas - up to 100 simultaneous tones
- ✓ different software feature codes available

### Precise - reliable - efficient

- ✓ easy handling and easy system configuration
- ✓ triggers corresponding trigger signals within a few milliseconds
- ✓ measurement profiles can be saved at any time and reloaded later on

# 4activeEQ-AVAD 3

## Performance

frame rate	up to 300fps
latency	down to 6.5ms (depending in configuration)
input power	9-36V DC
cooling	passive (no fan)
CAN Baudrate	up to 666,67

## Dimensions

size	320x320x85mm
weight	7,5kg

## Specification

- ✓ minimal latency times (according to NCAP specifications)
- ✓ 100 Hz frame rate (optional up to 300 fps)
- ✓ CAN-and LAN outputting rate 1 KHz maximum
- ✓ just a few milliseconds of information delay
- ✓ status signals activate the memory function



## Optional enhancements

- ✓ CAN interface with two channels for vehicle data
- ✓ up to 8 patterns, colours and colour search areas
- ✓ up to 100 simultaneous tones
- ✓ single measuring camera optional up to 300 fps
- ✓ LAN communications interface
- ✓ single result combinations logically linkable to an overall result
- ✓ triggering from bit patterns for ECU messages with latency time calculation

